

CLOUD 9 SILVER LINING

- CLOUD 9 APT CRUMB
- SUITABLE FOR HEAVY CONTRACT USE
- FOR USE IN DOUBLESTICK APPLICATIONS
- EASY PEEL APPEAL

RECOMMENDED AREAS OF USE

SUITABLE FOR HEAVY CONTRACT USE IN LARGE AREAS WHERE A FLAT FIRM FITTING IS REQUIRED.

SUITABLE FOR STRETCH-FIT OR DOUBLESTICK APPLICATIONS

Manufactured in the UK to BS EN 14499:2015

STANDARD SPECIFICATIONS		
TOP SURFACE	Printed Non-Woven	
BOTTOM SURFACE	Corona treated polymer film	
NOMINAL THICKNESS	6.00 mm	
NOMINAL ROLL WEIGHT	15.3 kg	33.7 lb
WEIGHT PER UNIT AREA	1015 g/m ²	30 oz/yd²
ROLL LENGTH	11.0 m	36.0 ft
ROLL WIDTH	1.37 m	54 in
GUARANTEE	Lifetime of the initial carpet installation (when used in recommended areas)	
CORE DENSITY	160 kg/m³	
PRODUCT DENSITY	169 kg/m³	

BS EN 14499 TEST RESULTS - BRITISH STANDARD FOR CARPET UNDERLAYS				
END USE CLASSIFICATION	BS EN 14499	HC/U		
WORK OF COMPRESSION AFTER 1000 IMPACTS	BS 4098	>90 J/m ²		
RETENTION OF WORK OF COMPRESSION	BS 4098	>90 %		
LOSS IN THICKNESS AFTER STATIC LOADING	BS 4939 ISO 3416	<5.00 %		
LOSS IN THICKNESS AFTER DYNAMIC LOADING	BS ISO 2094 (R05)	<5.00 %		
RESISTANCE TO CRACKING	BS EN 14499	Pass		

FIRE RESISTANCE TESTS		
HOT METAL NUT TEST	BS 4790	Pass - Low radius of effect
KLEINBRENNER TEST	DIN 54332	Pass - Burning Class T-a

INDOOR AIR QUALITY TEST	
TESTED TO ISO16000	
FRENCH VOC REGULATIONS	A+
FRENCH CMR COMPONENTS	Pass
ITALIAN CAM	Pass
FORMALDEHYDE EMISSION CLASS	E1

OTHER RELEVANT TESTS		
THERMAL RESISTANCE (TOG RATING)	BS 4745	1.5 TOG
IMPACT SOUND IMPROVEMENT INDEX		31 dB
(Test/Rated to BS EN ISO 140-8 / BS EN ISO 717-2)		



ISSUE 8 30-UNE-20